ΚΛ/Κ

ENGAGE **THE EXTREME** ELEMENTS.



MATERIAL

EXTERNAL SHELL: PC-PBT INTERNAL SHELL: HD Polystyrene + Thermoformed Polystirene cover ADJUSTMENT SYSTEM: FR nylon



SIZE Universal-adjustable from 52 to 63 cm



WEIGHT 670 g

STANDARD

EN 16471 | Helmets for wildland fire fighting EN 16473 | Helmets for technical rescue Complies with requirements of EN 12492 except for Clause 4.1.4. Ventilation

🗗 🞯 🕩 (in







TECHNOLOGIES

- > ACRYLIC CHINSTRAP FR Fire-resistant, low flammability, non-melting, and self-extinguishing.
- > QUICK RELEASE FASTENER Enables quick, easy helmet removal with gloved hands.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- > DRY+ LINER Moisture-wicking fabric that enhances wearer comfort.
- > CLICK-IN SYSTEM Attachment system that lets padding easily snap in and out.
- > HD EPS INTERNAL SHELL + THERMOFORMED PS COVER Impact absorbing inner shell with cover for added durability.
- **REFLECTIVE DECALS** designed for low visibility conditions.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.



451

450

PRODUCT OF ITAL