WVI00030



Fire-resistant, scratch-resistant, and anti-fog polycarbonate eye protection. Requires Easy Click Adapters FR. Can be worn with corrective glasses. Compatible with all Quantum helmets. Meets EN 14458 Standard.

The ZEN PLUS VISOR mounted on the QUANTUM helmet, via the EASY CLICK ADAPTERS FR, makes the helmet usable for use in wildland firefighting (EN16471) and technical rescue activities (EN16473) where there is potential exposure to flames.

TECHNICAL DETAILS

TEMPERATURE OF USE



MATERIAL Polycarbonate

-30°C / +50°C

OPTICAL CLASS



STANDARD

EN 14458

EN 166

EN 170 (clear)

EN 172 (smoke, mirror)

ANSI Z87.1



WEIGHT 80 g



CATEGORY

TECHNOLOGIES



Equipped with an anti-fog treatment to increase wearer visibility when active and in a variety of conditions.



Designed with a rubber upper contour to keep out sweat moisture and to enhance comfort.



CUT PROOF EDGE

Designed with a cut proof edge for enhanced comfort and safety.



PANORAMIC LENS

Wide view lens for optimal protection and visibility.



SCRATCH RESISTANT

Equipped with a scratch-resistant treatment for increased durability.



COMPATIBLE WITH GLASSES

Designed for use over corrective glasses.



EASY CLICK ADAPTERS FR

Fire-resistant and designed to easily attach and remove KASK eye and face protection accessories. Compatible with all Quantum

MARKINGS

CODE	COLOR	MARKINGS
WVI00030-500		EN14458:2018 KASK ZEN PLUS 10/2022 = ● BTKN 2C-1,2 -30°C+50°C E1/E3 CE 2754 UKCA 2C-1,2 KASK EN166 1BTKN / ANSI Z87+ U6 X D3
WVI00030-510		EN14458:2018 KASK ZEN PLUS 10/2022 = • BTKN 5-1,4 -30°C+50°C E1/E3 CE 2754 UKCA 5 -1,4 KASK EN166 1BTKN / ANSI Z87+ U6 L1.5 X D3
WVI00030-520		EN14458:2018 KASK ZEN PLUS 10/2022 = ● BTKN 5-2,5 -30°C+50°C E1/E3 CE 2754 UKCA 5 -2,5 KASK EN166 1BTKN / ANSI Z87+ U6 L2.5 X D3

ADDITIONAL INFORMATION

GUARANTEE

3 years from date of purchase

10 years starting from the date of manufacture. Shelf life depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor. Do not rub the lens when dry.

ZEN PLUS VISOR COLLECTION



KIT ZEN PLUS VISOR



KIT ZEN PLUS VISOR SMOKE



KIT ZEN PLUS VISOR



WAC00074 EASY CLICK ADAPTERS FR

DISCOVER MORE





SCAN FOR COMPLETE COLLECTION











